



A

Patent Application
Docket No. 33361-00026USPT




IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re patent application of:

Viswanathan et al.

For: Method and Apparatus to Provide Facility and Module Redundancy in
Telecommunication Switching Equipment

BOX APPLICATION
Assistant Commissioner
for Patents
Washington, D.C. 20231

CERTIFICATE OF MAILING BY EXPRESS MAIL
"EXPRESS MAIL" Mailing Label No. EL063369185US
Date of Deposit: <u>March 25</u> , 1999
I hereby certify that this paper or fee is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231
Type or Print Name: Carol Marstaller
 Signature

Sir:

PATENT APPLICATION TRANSMITTAL LETTER

Transmitted herewith for filing, please find the following:

- X Specification, claims and abstract of the above-referenced patent application (total of 36 pages)
- X 6 sheet(s) of drawing(s) (X formal/ informal) (Figures 1-6)
- X Combined Declaration and Power of Attorney (signed)
- X An Assignment of the invention to: SAMSUNG ELECTRONICS CO., LTD.
- A verified statement claiming small entity status under 37 CFR 1.9 and 1.27.
- X Other (specify):
 - 1. Check in the amount of \$40.00 as filing fee for Assignment
 - 2. Acknowledgement postcard

09276346-030599

The filing fee has been calculated as shown below:

FOR: <u>LARGE ENTITY</u>	NO. FILED	NO. EXTRA	RATE	FEE
BASIC FEE				\$760
TOTAL CLAIMS	22 - 20	2	\$18	\$ 36
INDEPENDENT CLAIMS	4- 3	1	\$78	\$ 78
MULTIPLE DEPENDENT CLAIM(S) PRESENTED			\$260	\$ _____
TOTAL FEE:				\$874

____ Please charge my Deposit Account No. 10-0447 in the amount of \$_____ This sheet is attached in duplicate.

x A check in the amount of \$874.00 is attached. Please charge any deficiency or credit any overpayment to Deposit Account No. 10-0447.

X The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 10-0447 This sheet is attached in triplicate.

X Any additional filing fees required under 37 CFR 1.16 including fees for presentation of extra claims.

X Any additional patent application processing fees under 37 CFR 1.17 and under 37 CFR 1.20(d).


X The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 10-0447. This sheet is attached in duplicate.

X Any patent application processing fees under 37 CFR 1.17 and under 37 CFR 1.20(d).

____ The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).

X Any filing fees under 37 CFR 1.16 including fees for presentation of extra claims.

Date: March 24, 1999



Steven R. Greenfield
Registration No. 38,166

JENKENS & GILCHRIST
1445 Ross Avenue, Suite 3200
Dallas, Texas 75202-2799
214/855-4789

66330-0403450

Patent Application
Docket # 33361-00026USPT
STA.BNL.018

CERTIFICATE OF MAILING BY EXPRESS MAIL
"EXPRESS MAIL" Mailing Label No. <u>EL063369185US</u>
Date of Deposit: <u>March 25</u> , 1999
I hereby certify that this paper or fee is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231
Type or Print Name: <u>CAROL MARSTALLER</u>
<i>Carol Marstaller</i> Signature

METHOD AND APPARATUS TO PROVIDE FACILITY
AND MODULE REDUNDANCY IN
TELECOMMUNICATION SWITCHING EQUIPMENT

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to communication networks, and more specifically, to ATM (Asynchronous Transfer Mode) equipment having module redundancy for protecting network connections from failure.

Description of Related Art

ATM (Asynchronous Transfer Mode) high-speed switched networks have been proposed as a technology capable of integrating present digital services with new multimedia services, e.g., video on demand, live television from many sources, CD-quality music, LAN interconnection, and high-speed data transport for science and industry. To implement these different services, ATM networks are designed to handle a variety of traffic characteristics, e.g., constant rate, variable rate, and bursty, required for various real time, such as video conferencing, and non-real time, such as E-mail and web browsing, applications. The basic principles of ATM networks are well known to those skilled in the art and are discussed in numerous published references (see, for example, Andrew S. Tanenbaum, Computer Networks, Prentice Hall, 1996, 3rd ed.).

ATM switches transfer data using a cell switching technology. All data in an ATM network is transmitted

between the switches of the network in small, fixed size
53 byte long ATM cells having 5 bytes for a header and 48
bytes for the information or data payload. The header of
each cell contains a virtual connection identifier used
5 for routing the cells over the network. Each ATM cell
contains a two-part connection identifier in the cell
header: a Virtual Path Identifier (VPI) and a Virtual
Circuit Identifier (VCI). This two-part connection
identifier uniquely identifies an ATM virtual connection
10 on a physical interface.

ATM is a connection-oriented technology. That is,
a call is required by user A to user B, similar to a
telephone call, to set up a connection between the two
users. Once the connection path is established, all data
15 cells are transferred over the same connection path.
This guarantees that cells will be delivered in order.
Although ATM establishes a circuit between hosts, it
establishes this circuit internally using cell switching
technology. When a virtual circuit is established

between hosts, what really happens is that table entries storing routing information are made in each switch along the path between the hosts.

5 The following is an example of what happens when a user A connects to a user B. First, user A sends a call request to user B. The call request arrives at an ingress switch of the ATM network. Call control software located at the ingress switch uses NNI signaling procedures combined with NNI routing services to locate user B and establish a virtual connection over which user
10 A and user B exchange data.

Once a connection is established, data can be exchanged between User A and User B. Typically, the flow of data proceeds as follows. User A opens an application
15 on the computer of User A which sends data to User B. Network software at User A's side will receive the data from the application of user A, and arrange the data into packets. Each packet is arranged as a variable length sequence of 53 byte ATM cells carrying the data payload

preceded by a packet header cell containing information related to the application. The packets are sent over the ATM network cell by cell from User A to User B. The cells are reassembled into packets by software at User
5 B's end and presented to User B as an application packet.

ATM networks provide several mechanisms for assuring quality of service and regulating traffic flow and congestion. Traffic shaping and traffic congestion control have been proposed for ATM networks. In traffic
10 shaping, a quality of services contract is formed before data transmission between the customer and the network where the required transmission parameters are specified. For example, a customer could specify a requirement that data be transferred with a delay of 10 microseconds. In
15 turn, the customer is required to abide by conditions of the contract, e.g., to transmit below an agreed upon rate. Traffic policing functions, e.g., user parameter control (UPC) within the ATM network enforce the user's agreement to the terms in the contract.

5 The physical layer connection of ATM networks normally consists of optical fibers working on the SONET (Synchronous Optical Network) standard. A SONET system consists of transport network elements such as add/drop multiplexers (ADMs), multiplexers, and repeaters all connected by optical fiber. An ATM switch in a SONET network may have one or more SONET interface unit boards which extract ATM cells from the optical signals of the fiber pathways to allow the ATM processing and routing functions to be applied by the ATM switch.

10 In ATM networks, the reliability of the ATM switch is critical because malfunctioning ATM equipment may result in the failure of an individual permanent virtual circuit (PVC) and a switched virtual circuit (SVC) connections. Malfunctions of the ATM equipment are generally classified into two types of failures: facilities failure and equipment failure. A facility failure refers broadly to the failure of anything external to the equipment such as a failure of one of the

5 cables coming into the equipment, e.g., a fiber cut, or even connector problems. Someone could unplug a connector on the front of the equipment and that would be classified as a facility failure. An equipment failure includes any failure occurring within the electronics of the equipment itself (e.g. electronic failure).

10 It would be highly desirable to provide protection for ATM equipment or other communication switching equipment in order to preserve network reliability despite the above stated facility and equipment failures.

SUMMARY OF THE INVENTION

15 In order to overcome the above-stated problems, the present invention includes working circuitry configured to receive a first stream of cells and protection circuitry configured to receive a second stream of cells. Typically, the cells are ATM cells. The second stream is identical to the first stream. The protection circuitry and the working circuitry are functionally identical and

663200" 943260
synchronized to each other. A cross point switch is
configured to select a first stream and is further
configured to select and substitute a second stream for
the first stream upon detection of an error condition in
5 the working circuitry of the first stream.

The error condition may be a facility error
condition (e.g., a disconnected cable) or an equipment
error condition. An equipment error condition is a
failure which occurs internal to equipment (e.g., the
10 SONET Framer, the multiplexer, the user parameter control
unit, the router, and the failure of other circuitry
associated with the working circuitry and protection
circuitry).

In a further aspect of the present invention, the
15 working circuitry receives the first stream from an
optical signal and the protection circuitry receives the
second stream from the same optical signal.

In another aspect of the present invention, the
working circuitry is implemented on a first board and the

protection circuitry is implemented on a second board,
the first board being separate and distinct from the
second board.

In yet another aspect of the present invention, the
5 working circuitry includes a plurality of ATM units
performing ATM functions on the first stream and the
protection circuitry includes a plurality of identical
ATM units performing the same ATM functions on the second
stream. One of the ATM units may be a multiplexer, a
10 SONET framer, a router, a user parameter control unit,
and a signaling unit.

In yet another aspect of the present invention, a
first module has a plurality of ports wherein one or more
of the ports accepts their stream as input to the working
15 circuitry and the remaining ports may accept their stream
as input to the protection circuitry.

In still another aspect of the present invention, a
second module includes the protection circuitry and has
a plurality of ports wherein one of the ports accepts the

second stream as input into the protection circuitry and the remaining ports may accept their stream as input to the working circuitry.

In a further aspect of the present invention, an ATM
5 switch fabric has a plurality of input ports, a plurality of output ports, and is configured to transfer an ATM cell received from a cell stream of one of the input ports to any one of the output ports.

In still another aspect of the present invention,
10 input ports of the ATM switch fabric receives the ATM cells from a cell stream, either the first stream or the second stream as selected by the cross point switch.

In another aspect of the present invention, a second cross point switch is configured to receive ATM cells
15 from one of the output ports of the ATM switch fabric and directs the ATM cells to a third stream and further directs the ATM cells to a fourth stream.

In still another aspect of the present invention, a second working circuitry is configured to receive the

third stream of cells from the second cross point switch.
Furthermore, a second protection circuitry is configured
to receive the fourth stream of cells from the second
cross point switch. The third stream is identical to the
5 fourth stream. The second protection circuitry and the
second working circuitry are functionally identical and
synchronized to each other.

BRIEF DESCRIPTION OF THE DRAWINGS

10 FIGURE 1 is a system diagram showing an exemplary
ATM switch architecture using cross point switches to
provide protection against failures according to the
present invention.

FIGURE 2 is a block diagram of an exemplary SONET
15 Interface unit for operating on input ATM cell streams.

FIGURE 3 is a block diagram of an exemplary SONET
Interface unit for operating on output ATM cell streams.

FIGURE 4 is an exemplary system diagram of an ATM
switch architecture according to the present invention.

FIGURE 5 is an exemplary block diagram illustrating data flow directed by cross point switches according to the present invention.

FIGURE 6 is an exemplary block diagram illustrating signaling flow directed by cross point switches according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

FIGURE 1 shows a preferred embodiment of an architecture 100 of the present invention for protecting an ATM switching fabric 118 from facility and equipment malfunction. However, it should be understood that other embodiments of the present invention may be applied to switching fabrics other than ATM. The present invention provides protection on the order of 50 milliseconds for each individual permanent virtual circuit (PVC) and switched virtual circuit (SVC) of the ATM network. In brief, the manner in which this is accomplished is by using 1 + 1 APS (Automatic Protection Switching) to

provide identical information to two separate modules.
In the event of a failure, the protection module will
become active and provide service. The protection module
is made active to the switch fabric by using cross point
5 switches.

FIGURE 1 shows the architecture 100 having four
SONET (Synchronous Optical Network) interface modules
(SIU) 112, 114, 122, 124. The cross point switches 116
and 120 interface these four SIU modules to switch fabric
10 118. In the preferred embodiment, the circuitry of
modules 112 and 122 are implemented on the same circuit
board as transceiver pairs and similarly the circuitry of
redundant modules 114 and 124 are implemented on the same
circuit board as transceiver pairs. However, FIGURE 1
15 depicts the modules 112, 114, 122 and 124 functionally
and thus the present invention is not limited to any
particular correspondence between modules 112, 114, 122,
124 and circuit board hardware. Thus, other
configurations are possible. In addition, the circuitry

of the modules 112, 114, 122 and 124 are bidirectional.
Thus, even though data will be described herein as being
input into modules 112, and 114 flowing through the system
and output through modules 122 and 124, it should be
5 noted that data may also flow in the opposite direction
by being input to modules 122 and 124, and flowing
through the system and output through modules 112 and
114.

FIGURE 2 shows the preferred embodiment of SIU
10 module 112 receiving streams 131a-d of SONET frames on
ports 1-4. Redundant module 114 works identically to
module 112. In the preferred embodiment, streams 131a-d
are composed of SONET frames. A SONET frame is made up
of frame overhead information and a payload consisting of
15 a series of ATM cells. This process of supporting an
asynchronous ATM layer using a synchronous SONET carrier
is well-known in the telecommunications art.

SONET deframers 133a-d extract the ATM payloads from
the SONET frames of streams 131a-131d. The payload

extracted from each SONET frame is a stream of ATM cells.

On port 0 only, the SIU module 112 contains an AAL5
(ATM adaption layer 5) unit 131f receiving an ATM
electrical signal (non optical) 131e on port 0 from the
5 ATM network. AAL5 unit 131f performs the signaling
function by setting up and breaking down calls for the
ATM network. In the embodiment of the present invention,
there is one signaling function unit to serve four ports
of each module. Future revisions or variations of the
10 SIU modules are not necessarily constrained to this
configuration. Multiplexer unit 135a combines the ATM
signal from the output of AAL5 131f with the stream of
ATM cells output from the SFM 133a.

Multiplexer units 135a-135d pass the data flow
15 received from the SONET deframers (SFM units) 133a-133d
and AAL5 131f to the Parametric Control (UPC) units 137a-
d which monitor the ATM cells streams received from units
135a-135d to enforce customer contracts and perform other
policing functions well-known in the ATM network art.

The routers 139a-d route the ATM cells received from
UPC units 137a-137d from the input ports 119 of switch
fabric 118 to the appropriate output ports 121 of switch
fabric 118 (see FIGURE 1). Each ATM cell has a header
5 and a payload carrying information bits. The header of
the ATM cell indicates a virtual address from which the
router determines where to route the ATM cell. For
example, an ATM cell input to port 1 of the ATM switch
fabric 118 will be routed to one of switch fabric output
10 ports 1-8 depending on the header. The router will place
an internal code in the ATM cell for routing the cell
through the switch fabric 118.

FIGURE 3 shows SIU module 122 operating on ATM cell
streams 141a-d received from crosspoint switch 120 output
15 ports 1-4 (in the default case where ports 1-4 are the
working ports). Routers 143a-143d may perform operations
on ATM cells streams 141a-d to prepare them for routing
to the external network. Then UPC units 145a-145d may
perform traffic shaping or other operations on the cell

stream output from routers 143a-143d. The multiplexers
147a-147d pass the data through from UPC units 145a-145d.
In port 0, demultiplexer 147a separates the call signal
data from the ATM data stream to signaling unit 142. SFM
5 modules 149a-149d create SONET frames for transporting
the ATM cells received from MUX 147a-147d. In addition,
it should be noted that modules 122 and 124 are
bidirectional and therefore router units (RT) 143a-143d,
UPC 145a-145d, MUX 147a-147d, SFM 149a-149d, and AAL5
10 unit 142 of modules 122, 124 perform the same functions
described above for the units of modules 112, 114 when
ATM signal streams 151a-151d are received on ports 1-4.

SIU module 114 is a redundant module having
identical circuitry to SIU 112. Similarly, SIU module
15 124 is a redundant module containing identical circuitry
to SIU module 122. The interface modules 112 and 122 are
designated as the active modules. The interface modules
114 and 124 are designated as the standby modules. At
any given time, a port of one of the modules can be

configured to be either a working port or a protected
port. The working port is actively processing input data
while the protected port remains inactive. To clarify
this, for example, either port 1 of SIU module 112 or
5 port 1 of module 114 will be the working port and the
other port will be the protected port. Similarly port 2
of SIU module 112 can be the working port while port 2 of
SIU module 114 is the protected port or vis-a-vis. In
the present exemplary embodiment all the ports of the
10 active SIU module 112 are initially chosen as the working
ports and all the ports of the SIU module 114 are
protected ports. Referring again to FIGURE 1, the
switching fabric 118 is capable of routing an ATM cell
from any one of the 8 input ports 119 to any one of the
15 8 output ports 121 (8 ports are shown in Figure 1 for
simplification). The ATM switch, in general, may have an
arbitrary number of inputs (N), that is, it could be an
N x N matrix. Preferably, there are 16 input and output
ports.

There are two cross-point switches 116, 120, the cross point switch 116 on the input stage of the switch fabric 118 and the cross-point switch 120 on the output stage of the switch fabric 118. The cross point switch 116 having input ports and output ports connects any of its input ports 136 to any of its output ports 117. The cross point switch 120 connects any of its input ports 123 to any of its output ports 141.

FIGURE 4 illustrates the basic architecture 100 of the present invention in more detail than FIGURE 1 by including the circuitry of the SIU modules shown in FIGURES 2 and 3.

FIGURE 5 illustrates the data flow operation of cross point switches 116 and 120 according to an exemplary embodiment of the present invention. In this particular configuration, ports 1 and 2 of SIU module 112 and port 3 of redundant SIU module 114 are the current working ports. Port 4 is not being used in this example.

In fact, it is possible to have port 4 for both SIU 122 and SIU 124 to be operated in an unprotected mode.

The data flows of Figure 5 will now be explained. First, ATM cell stream 131a received at port 1 of SIU module 112 is processed by the SONET deframer 133a, the MUX 135a, UPC unit 137a, and router 139a and output as ATM cell stream 136a. Cross point switch 116 directs ATM cell stream 136a from input port 1 to output port 1 of cross point switch 116 along path 201 so that the cell stream connects to and is received by port 1 of switch fabric 118.

ATM cell stream 131b is received at port 2 of SIU module 112 and processed by SONET deframer 133b, MUX 135b, UPC unit 137b, and router 139b and output as ATM cell stream 136b. Cross point switch 116 directs ATM cell stream 136b from its input port 2 to its output port 2 along path 207 so that the cell stream connects to and is received by port 2 of switch fabric 118.

5 ATM cell stream 131c received at port 3 of SIU
module 114 are processed by SONET deframer 133c, MUX
135c, UPC unit 137c, and router 139c and output as ATM
cell stream 136c. Cross point switch 116 directs ATM
cell stream 136c from input port 7 to output port 3 of
the cross point switch 116 along path 213 so that the
cell stream connects to and is received by input port 3
of switch fabric 118. Thus, the cross point switch 116
connects redundant module 114 output port 7 to input port
3 of switch fabric 118 in substitution for the default
path, which when operative, connects port 3 of SIU module
112 to input port 3 of switch fabric 118.

10
15 The ATM cell stream 131a is also provided to input
port 1 of SIU module 114. If there is an equipment
failure in port 1 path in SIU 112, then the communication
can be switched and is being processed by port 1 of SIU
module 114 and routed via crosspoint switch 116 to input
port 1 of the switch fabric 118 without dropping the
call. In effect the call is resetup on the fly without

interruption to the user. This is an advancement in ATM network switching because the crosspoint switch handles equipment failures without dropping a communication or call.

5 In essence, an exemplary embodiment of the present invention can detect an equipment failure, such as in an SIU module (the working circuitry) and then protect against the failure by rerouting the ATM cell data from another SIU module's input (the protected circuitry) by
10 disconnecting ATM cell data from a failed, working SIU and connecting a working protection SIU to the switch fabric by using the crosspoint. The crosspoint switch allows the rerouted cell data to be placed back on its original path through the switch fabric. The user does
15 not have his call dropped in the event of the equipment failure. Thus, a more reliable ATM switch network is established.

Switch fabric 118 routes ATM cells received at its input ports 119 to its output ports 121 in accordance

with routing instructions. ATM cells destined for output
port 1 of switch fabric 118 form ATM cell stream 141a.
ATM cells of cell stream 141a composed of ATM cells
routed to output port 1 by ATM switch 118 are then
5 directed by cross point switch 120 along path 203 to
input port 1 of SIU 122 and concurrently are directed
along path 205 to output port 5 of cross point switch 120
which connects directly to port 1 of SIU 124.
Consequently, identical ATM streams are transported over
10 paths 203 and 205 by cross point switch 120 to port 1 of
SIU modules 122 and 124. Thus, this provides redundant
paths to support one-plus-one (1 + 1) SONET protection
switching.

ATM cells destined for output port 2 of switch
15 fabric 118 form ATM cell stream 141b. ATM cells of cell
stream 141b composed of ATM cells routed to output port
2 by ATM switch 118 are then directed by cross point
switch 120 along path 209 to port 2 of SIU 122 and
concurrently are directed along path 211 to output port

6 of cross point switch 120 which connects directly to
port 2 of SIU 124. ATM cells destined for output port 3
of switch fabric 118 form ATM cell stream 141c. ATM
cells of cell stream 141c composed of ATM cells routed to
output port 3 by ATM switch 118 are then directed by
cross point switch 120 along path 215 to port 3 of SIU
122 and concurrently are directed along path 217 to port
7 of cross point switch 120 which connects directly to
port 3 of SIU 124.

FIGURE 6 demonstrates an example of signaling data
flow in an exemplary embodiment of the present invention
as would appear during a call setup. In this particular
configuration, ports 1 and 2 of SIU module 112 and Port
3 of redundant SIU module 114 are the current active
ports. Note that Port 4 is not being used in this
example.

ATM cell stream 131a received at port 1 of SIU
module 112 is processed by SFM 133a, MUX 135a, UPC 137a,
and RT 139a and output as ATM cell stream 136a. Cross

point switch 116 directs ATM cell stream 136a from its port 1 to its port 1 along path 301 so that the cell stream connects to and is received by port 1 of switch fabric 118.

5 The ATM cell stream 131b received at port 2 of SIU module 112 is processed by SFM 133b, MUX 135b, UPC 137b, and RT 139b and output as ATM cell stream 136b. Cross point switch 116 directs ATM cell stream 136b from its port 2 to its port 2 along path 303 so that the cell stream connects to and is received by port 2 of switch fabric 118.

10 The ATM cell stream 131c received at the input port 3 of SIU module 114 is processed by SFM 133c, MUX 135c, UPC 137c, and RT 139c and output as ATM cell stream 136c. Cross point switch 116 directs ATM cell stream 136c from its input port 7 to its output port 3 along path 305 so that the cell stream connects to and is received by input port 3 of switch fabric 118.

5 The switch fabric 118 routes the ATM signaling cells
from paths 301, 303, 305, along paths 307, 309, and 311
to output port 1 on switch fabric 118. Thus, all the
call setup information for ports 1, 2 and 3 are being
routed to port 1 along path 312 to the signaling unit
AAL5 142 of SIU module 122 which processes the calls.
Note that it is possible to cause a failure of AAL5 142
on SIU module 122 to use AAL5 142 on SIU module 124.

10 Although only certain embodiments of the apparatus
of the present invention have been illustrated in the
accompanying Drawings and described in the foregoing
Detailed Description, it will be understood that the
invention is not limited to the embodiments disclosed,
but is capable of additional rearrangements,
15 modifications and substitutions without departing from
the spirit of the invention as set forth and defined by
the following claims. Accordingly, it should be
understood that the scope of the present invention

encompasses all such arrangements and is solely limited
by the claims as follows.

11/11/2011 11:11:11

WHAT IS CLAIMED IS:

1 1. An apparatus providing equipment and facility
2 redundancy, comprising:
3 working circuitry configured to receive a first
4 stream of communication data;
5 protection circuitry configured to receive a
6 second stream of communication data, the second stream
7 being identical to the first stream, the protection
8 circuitry and the working circuitry being functionally
9 identical and synchronized to each other; and
10 a cross point switch configured to select from
11 one of the first stream and the second stream and further
12 configured to select and substitute the second stream for
13 the first stream upon detection of an error condition in
14 at least one of the working circuitry and the first
15 stream of communication data.

1 2. The apparatus of claim 1, wherein the
2 communication data is ATM cells data.

1 3. The apparatus of claim 1, wherein the working
2 circuitry receives the first stream from an optical
3 signal and the protection circuitry receives the second
4 stream from the optical signal.

1 4. The apparatus of claim 1, wherein the working
2 circuitry is implemented on a first circuit board and the
3 protection circuitry is implemented on a second circuit
4 board, the first circuit board being separate and
5 distinct from the second circuit board.

1 5. The apparatus of claim 1, wherein the working
2 circuitry includes a plurality of first ATM channels
3 performing ATM functions on the first stream and the
4 protection circuitry includes a plurality of second ATM

5 channels performing the ATM functions on the second
6 stream.

1 6. The apparatus of claim 5, wherein one of the
2 first ATM channels and one of the second ATM channels
3 each include a multiplexer.

1 7. The apparatus of claim 5, wherein one of the
2 first ATM channels and one of the second ATM channels
3 includes a SONET framer.

1 8. The apparatus of claim 5, wherein one of the
2 first ATM channels and one of the second ATM channels
3 includes a router.

1 9. The apparatus of claim 5, wherein one of the
2 first ATM channels and one of the second ATM channels
3 includes a user parameter control unit.

1 10. The apparatus of claim 1, further comprising:
2 a first module including the working circuitry
3 and having a plurality of ports wherein one of the ports
4 accepts the first stream as input to the working
5 circuitry.

6
7 11. The apparatus of claim 1, further comprising:
8 a second module including the protection
9 circuitry and having a plurality of ports wherein one of
10 the ports accepts the second stream as input into the
11 protection circuitry.

1 12. The apparatus of claim 1, further comprising:
2 an ATM switch fabric having a plurality of
3 input ports, a plurality of output ports, and configured
4 to transfer an ATM cell from one of said plurality of
5 input ports to anyone of said plurality of output ports,
6 said ATM cell being received from said working circuitry
7 as part of said first stream.

1 13. The apparatus of claim 1, further comprising:
2 an ATM switch fabric having a plurality of
3 input ports, a plurality of output ports, and configured
4 to transfer an ATM cell from one of said plurality of
5 input ports to anyone of said plurality of output ports,
6 said ATM cell being received from said protection
7 circuitry as part of said second stream.

1 14. The apparatus of claim 12, further comprising:
2 a second cross point switch configured to
3 receive ATM cells from one of the plurality of output
4 ports of the ATM switch fabric and to direct the received
5 ATM cells to one of an output portion of a second working
6 circuitry and an output portion of a second protection
7 circuitry.

1 15. The apparatus of claim 1, wherein the error
2 condition is a facility error condition.

1 16. The apparatus of claim 15, wherein the facility
2 error condition includes a disconnected cable.

1 17. The apparatus of claim 1, wherein the error
2 condition is an equipment error condition.

1 18. The apparatus of claim 17, wherein the
2 equipment error condition includes at least one of a
3 failure of a SONET Framer a failure of a multiplexer, a
4 failure of a parameter control unit, and a failure of a
5 router.

1 19. A method providing equipment and facility
2 redundancy for ATM circuitry which carries out ATM
3 functions, comprising:

4 performing a group of ATM functions with first
5 circuitry on a first stream of ATM cells producing a
6 processed first stream;

7 performing the ATM functions with second
8 circuitry on a second stream of ATM cells producing a
9 processed second stream, the second stream being
10 identical to the first stream, the first circuitry and
11 the second circuitry implementing the ATM functions, the
12 first circuitry and the second circuitry being
13 synchronized to each other; and

14 substituting the second processed stream for
15 the first processed stream for input to a designated port
16 of an ATM switch upon detection of an error condition in
17 the first circuitry, the first processed stream having
18 initially been selected for input to the designated port
19 of the ATM switch, thereby providing redundancy
20 protection for the ATM functions.

1 20. The method of claim 19, wherein the ATM
2 functions include at least one of multiplexing, SONET
3 framing, routing, and user parameter control.

1 21. A method providing equipment and facility
2 redundancy for ATM circuitry, comprising the steps of:
3 receiving a first stream of ATM cells;
4 forming a second stream of ATM cells identical
5 to the first stream of ATM cells;
6 detecting an error condition associated with
7 the first stream; and
8 switching from the first stream to the second
9 stream upon detection of the error condition.

1 22. A method of providing equipment and facility
2 redundancy of ATM circuitry, comprising the steps of:
3 using a crosspoint switch to duplicate ATM
4 calls; and
5 using said crosspoint switch to send redundant
6 cells to two different paths.

ABSTRACT

A cross point switch is configured to select from one of a first stream of ATM cells and a second stream of ATM cells, the first stream and the second stream being identical, and is further configured to select and substitute the second stream for the first stream upon detection of an error condition in the working circuitry operation on the first stream. The working circuitry, which is located on an interface module, is configured to receive and operate on the first stream of ATM cells. The protection circuitry, which is located on a redundant interface module, is configured to receive and operate on the second stream of cells. The protection circuitry and the working circuitry are functionally identical and synchronized to each other so that switching occurs from one stream to the other without interruption of network service.




FIG. 1

100




FIG. 2

112




FIG. 3

122





FIG. 4






FIG. 5




FIG. 6

RULES 63 AND 67 (37 C.F.R. 1.63 and 1.67)
DECLARATION AND POWER OF ATTORNEY

FOR UTILITY/DESIGN/CIP/PCT NATIONAL APPLICATIONS

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; and

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **METHOD AND APPARATUS TO PROVIDE FACILITY AND MODULE REDUNDANCY IN TELECOMMUNICATION SWITCHING EQUIPMENT**, the specification of which: (mark only one)

- X (a) is attached hereto.
 (b) was filed on as Application Serial No. and was amended on (if applicable)
 (c) was filed as PCT International Application No. PCT/ on and was amended on (if applicable).
 (d) was filed on as Application Serial No. and was issued a Notice of Allowance on .
 (e) was filed on and bearing attorney docket number

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above or as allowed as indicated above.

I acknowledge the duty to disclose all information known to me to be material to the patentability of this application as defined in 37 CFR § 1.56. If this is a continuation-in-part (CIP) application, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the Office all information known to me to be material to patentability of the application as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this CIP application.

I hereby claim foreign priority benefits under 35 U.S.C. § 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate filed by me or my assignee disclosing the subject matter claimed in this application and having a filing date (1) before that of the application

STA.BNL.018
33361-00026USPT

PATENT APPLICATION

on which my priority is claimed or, (2) if no priority is claimed, before the filing date of this application:

PRIOR FOREIGN PATENTS

<u>Number</u>	<u>Country</u>	<u>Month/Day/Year</u> <u>Filed</u>	<u>Date first laid-</u> <u>open or</u> <u>Published</u>	<u>Date</u> <u>patented or</u> <u>Granted</u>	<u>Priority Claimed</u> <u>Yes</u> <u>No</u>
---------------	----------------	---------------------------------------	---	---	---

I hereby claim the benefit under 35 U.S.C. § 120/365 of any United States application(s) listed below and PCT international applications listed above or below:

PRIOR U.S. OR PCT APPLICATIONS

<u>Application No. (series code/serial no.)</u>	<u>Month/Day/Year Filed</u>	<u>Status(pending, abandoned, patented)</u>
---	-----------------------------	---



I hereby appoint JOHN HAN, Reg. No. 41,403; THOMAS L. CRISMAN, Reg. No. 24,846; THOMAS L. CANTRELL, Reg. No. 20,849; STANLEY R. MOORE, Reg. No. 26,958, H. MATHEWS GARLAND, Reg. No. 19,129; GERALD T. WELCH, Reg. No. 30,332; ROGER L. MAXWELL, Reg. No. 31,855; P. WESTON MUSSELMAN, JR., Reg. No. 31,644; JERRY R. SELINGER, Reg. No. 26,582; J. KEVIN GRAY, Reg. No. 37,141; STEVEN R. GREENFIELD, Reg. No. 38,166; ANDRE M. SZUWALSKI, Reg. No. 35,701; STUART D. DWORK, Reg. No. 31,103; CRAIG A. HOERSTEN, Reg. No. 38.917; RICHARD J. MOURA, Reg. No. 34,883; RICHARD A. MYSLIWIEC, Reg. No. 40,098; RAYMOND VAN DYKE, Reg. No. 34,746; BRIAN D. WALKER, Reg. No. 37.751; and J. PAT HEPTIG, Reg. No. 40,643, all of the firm of **JENKENS & GILCHRIST, P.C.**, 3200 Fountain Place, 1445 Ross Avenue, Dallas, Texas 75202-2799, as my attorneys and/or agents, with full power of substitution and revocation, to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith, and to file and prosecute any international patent application filed thereon before any international authorities under the Patent Cooperation Treaty, and I hereby authorize them to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/organization who/which first sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct them in writing to the contrary.

Please address all correspondence and direct all telephone calls to:

Steven R. Greenfield
Jenkins & Gilchrist, A Professional Corporation
3200 Fountain Place
1445 Ross Avenue
Dallas, Texas 75202-2799
214/855-4789 Fax: 214/855-4300

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAMED INVENTOR(S)

1	SENTHIL K. VISWANATHAN		3-17-99
	Full Name	Inventor's Signature	Date
	530 Burton Road, Apt. 1114 Richardson, Texas 75081 Residence (city, state, country)	3440 - LEBON DRIVE, # 4214 SAN DIEGO CA - 92122	INDIAN Citizenship
2	ROBERT W. CUBBAGE		march 4, 1999
	Full Name	Inventor's Signature	Date
	804 Fawnvalley Drive Allen, Texas 75002 Residence (city, state, country)	3440 - LEBON DRIVE, # 4214 SAN DIEGO, CA - 92122	USA Citizenship
	804 Fawnvalley Drive Allen, Texas 75002 Post Office Address (include zip code)		

Please address all correspondence and direct all telephone calls to:

Steven R. Greenfield
Jenkins & Gilchrist, A Professional Corporation
3200 Fountain Place
1445 Ross Avenue
Dallas, Texas 75202-2799
214/855-4789 Fax: 214/855-4300

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAMED INVENTOR(S)

1	SENTHIL K. VISWANATHAN		
	Full Name	Inventor's Signature	Date
	530 Burton Road, Apt. 1114 Richardson, Texas 75081 Residence (city, state, country)		
2	ROBERT W. CUBBAGE	<i>Robert W. Cubbage</i>	March 7, 1999
	Full Name	Inventor's Signature	Date
	804 Fawnvalley Drive Allen, Texas 75002 Residence (city, state, country)		
2	804 Fawnvalley Drive Allen, Texas 75002	USA	
	Post Office Address (include zip code)	Citizenship	
	804 Fawnvalley Drive Allen, Texas 75002 Post Office Address (include zip code)		